

Preferred Shoulder Diameters

بلبرینگ اشکان

NRJ BEARING

Bearing No.	Nominal Bearing Dimensions			Preferred Shoulder Diameters				Basic Load Ratings (lbs)		Factor	Limiting Speeds (1000 RPM)		Ball Complement		Bearing Weight (Approx.)
	d	D	Open	Preferred Shoulder Diameters				C_r	C_{or}		Grease rpm	Oil rpm	No.	Size mm	Weight
	mm	mm	mm	r (min)	da (min)	da (max)	Da (max)	KN	KN					lbs	kg
6201 1/2	12.7	32	10	0.6	15.1	17	27	6.8	3.1	12.3	23000	28000	7	5.953	0.0792
6202 5/8	15.88	35	11	0.6	18.5	19	30	7.75	3.6	13.2	20000	25000	8	5.953	0.1012
6202-16	16	35	11	0.6	18.8	19	30	7.75	3.6	13.2	20000	25000	8	5.953	0.1012
6203 5/8	15.88	40	12	0.6	19.1	23.5	35.1	9.6	4.6	13.2	18000	22000	8	6.747	0.143
98205	25	52	9	1	28.2	...	8.8	10.6	6.6	15	18000	28000	11		0.1804
SC205	25	52	14	1	30.6	...	6.4	13.8	7.6	14	18000	28000	9	7.938	0.264
SC0563	25	62	12	1.1	32	...	5	12.81	8.4	12	16000	24000	9	8.731	0.3916
62/22	22	50	14	1	27	29.5	45	12.9	6.8	13.5	14000	17000	9	7.144	0.258
63/22	22	56	16	1.1	28.5	30.5	49.5	18.4	9.3	12.4	13000	15000	7		0.3946
63/22A	22	56	15	1.1	28.5	30.5	49.5	18.4	9.3	12.4	13000	15000	7		0.3946
63/28	28	68	18	1.1	35	38.5	1	26.7	14	13	11000	13000	8		0.6512
63/28A	28	68	17	1.1	35	38.5	1	26.7	14	13	14000	22000	8		0.6512
B15-70	15	32	11	0.3	17	19	30	5.85	2.9	13.9	25000	29000	9	4.763	0.066
B14-42	14	42	13	1	19.8	23	37	11.9	5.5	12.3	19000	22000	7	7.938	0.1804
402082	30	72	19	1.1	36.5	43	65.5	28.1	16	13.3	7900	6000	8		0.7678